

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

1 Identification

- **Product identifier**
- **Trade name:** *AT-2010 Part B*
- **Relevant identified uses of the substance or mixture.** *Activator*
- **Application of the substance / the mixture** *Activator*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Weld Mount System
63 Epping Road
Raymond, NH 03077*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:**
*ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 1)

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**




Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture**

- **Hazardous components:**

| | | |
|----------|---------------------------|---------|
| 80-62-6 | methyl methacrylate | 25-50% |
| | Aldehyde-Amine Condensate | 2.5-10% |
| 108-88-3 | toluene | ≤1% |

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- **After swallowing:**
Rinse mouth with water.
Do not induce vomiting. Obtain medical advice.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam
CO₂, sand, extinguishing powder. Do not use water.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

| · PAC-1: | | |
|----------|---------------------|-----------|
| 80-62-6 | methyl methacrylate | 17 ppm |
| 108-88-3 | toluene | 67 ppm |
| · PAC-2: | | |
| 80-62-6 | methyl methacrylate | 120 ppm |
| 108-88-3 | toluene | 560 ppm |
| · PAC-3: | | |
| 80-62-6 | methyl methacrylate | 570 ppm |
| 108-88-3 | toluene | 3700* ppm |

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep container closed when not in use.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store below 32C [89.6F]

Store in a cool location away from direct heat.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

· **Further information about storage conditions:**

Protect from heat and direct sunlight.

Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

| 80-62-6 methyl methacrylate | |
|-----------------------------|--|
| PEL | Long-term value: 410 mg/m ³ , 100 ppm |
| REL | Long-term value: 410 mg/m ³ , 100 ppm |
| TLV | Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm |
| DSEN | |

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 4)

108-88-3 toluene

| | |
|------------|---|
| PEL | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 75 mg/m ³ , 20 ppm BEI |

· **Ingredients with biological limit values:****108-88-3 toluene**

| | |
|------------|--|
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment (see listings below)**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 5)

- **Eye protection:**
Safety glasses with side shields.



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

| | |
|------------------------|-----------------|
| Form: | Paste |
| Color: | Yellow |
| Odor: | Characteristic |
| Odor threshold: | Not determined. |

- **pH-value:** Not determined.

- **Change in condition**

| | |
|-----------------------|--------------------|
| Melting point: | Undetermined. |
| Boiling point: | > 100 °C (>212 °F) |

- **Flash point:** 14 °C (57.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 430 °C (806 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Flammable limits:**

| | |
|---------------|------------|
| Lower: | 2.1 Vol % |
| Upper: | 12.5 Vol % |

- **Vapor pressure at 20 °C (68 °F):** 47 hPa (35.3 mm Hg)

- **Specific gravity at 20 °C (68 °F):** 1.03 g/cm³ (8.59535 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

| | |
|-------------------|-----------------|
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 6)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Polymerization may occur upon loss of inhibitor.
- **Conditions to avoid**
Heat, flames, sparks, hot surfaces, ignition sources.
DO NOT mix in batches greater than 100 grams unless you plan to use immediately.
- **Incompatible materials:**
Reacts with oxidizing agents.
reducing agents.
- **Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide
Acrylic Monomer

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **LD/LC50 values that are relevant for classification:**
- | | | |
|-----------------------------|------|-------------------|
| 80-62-6 methyl methacrylate | | |
| Oral | LD50 | 7,872 mg/kg (rat) |
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
 - **Sensitization:** Skin Contact - Sensitization possible through skin contact.
 - **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|----------|---------------------|---|
| 80-62-6 | methyl methacrylate | 3 |
| 108-88-3 | toluene | 3 |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p style="text-align: right;">UN1133</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p style="text-align: right;">Adhesives ADHESIVES</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">3 Flammable liquids 3</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">3 Flammable liquids 3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | <p style="text-align: right;">II</p> |
| <ul style="list-style-type: none"> · Environmental hazards: | <p style="text-align: right;">Not applicable.</p> |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: | <p style="text-align: right;">Warning: Flammable liquids 33 F-E,S-D</p> |

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 8)

- | | |
|--|--------------------------|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN1133, Adhesives, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

| | |
|--|--|
| · Section 355 (extremely hazardous substances): | |
|--|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| | |
|--|--|
| · Section 313 (Specific toxic chemical listings): | |
|--|--|

| | | |
|---------|---------------------|--|
| 80-62-6 | methyl methacrylate | |
|---------|---------------------|--|

| | | |
|----------|---------|--|
| 108-88-3 | toluene | |
|----------|---------|--|

| | |
|---|--|
| · TSCA (Toxic Substances Control Act): | |
|---|--|

| |
|--|
| All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements. |
|--|

| | |
|-------------------------|--|
| · Proposition 65 | |
|-------------------------|--|

| | |
|---|--|
| · Chemicals known to cause cancer: | |
|---|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| | |
|--|--|
| · Chemicals known to cause reproductive toxicity for females: | |
|--|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| | |
|--|--|
| · Chemicals known to cause reproductive toxicity for males: | |
|--|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| | |
|---|--|
| · Chemicals known to cause developmental toxicity: | |
|---|--|

| | | |
|----------|---------|--|
| 108-88-3 | toluene | |
|----------|---------|--|

| | |
|---|--|
| · (DSL) Canada Domestic Substance List | |
|---|--|

| |
|--|
| All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements. |
|--|

| | |
|---|--|
| · New Jersey Right-to-Know List: | |
|---|--|

| | | |
|---------|---------------------|--|
| 80-62-6 | methyl methacrylate | |
|---------|---------------------|--|

| | | |
|----------|---------|--|
| 108-88-3 | toluene | |
|----------|---------|--|

| | |
|---|--|
| · New Jersey Special Hazardous Substance List: | |
|---|--|

| | | |
|---------|---------------------|--------|
| 80-62-6 | methyl methacrylate | F3, R2 |
|---------|---------------------|--------|

| | | |
|----------|---------|--------|
| 108-88-3 | toluene | TE, F3 |
|----------|---------|--------|

| | |
|---|--|
| · Pennsylvania Right-to-Know List: | |
|---|--|

| | | |
|---------|---------------------|--|
| 80-62-6 | methyl methacrylate | |
|---------|---------------------|--|

| | | |
|----------|---------|--|
| 108-88-3 | toluene | |
|----------|---------|--|

| | |
|---|--|
| · Pennsylvania Special Hazardous Substance List: | |
|---|--|

| | | |
|---------|---------------------|---|
| 80-62-6 | methyl methacrylate | E |
|---------|---------------------|---|

| | | |
|----------|---------|---|
| 108-88-3 | toluene | E |
|----------|---------|---|

| | |
|-----------------------------------|--|
| · Cancerogenity categories | |
|-----------------------------------|--|

| | |
|--|--|
| · EPA (Environmental Protection Agency) | |
|--|--|

| | | |
|---------|---------------------|-------|
| 80-62-6 | methyl methacrylate | E, NL |
|---------|---------------------|-------|

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 03/30/2018

Revision Number 1

Revision Date 03/30/2018

Trade name: AT-2010 Part B

(Contd. of page 9)

| | | |
|---|---------------------|----|
| 108-88-3 | toluene | II |
| · TLV (Threshold Limit Value established by ACGIH) | | |
| 80-62-6 | methyl methacrylate | A4 |
| 108-88-3 | toluene | A4 |
| · MAK (German Maximum Workplace Concentration) | | |
| None of the ingredients is listed. | | |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| None of the ingredients is listed. | | |

· **National regulations:**

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- **Department issuing SDS:** Environment protection department.
- **Creation Date:** 03/30/2018
- **Date of preparation / last revision** 03/30/2018 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

USA